

# The Light Source

## Mega-Coupler



The Mega-Coupler has a 1/2" x 1 1/4" Hex Head Bolt with The Light Source Wing Nut.

Our Mega-Coupler has solid nut tabs that won't break off. It uses standard 1/2 inch by 1-1/4 inch long hex head grade 8 bolts to secure your load. The bolt head locks into the hex milled pocket so that you can tighten the nyloc nut while the damp is installed. The Mega-Coupler fastens from (1-1/4" Pipe) 1.66" OD to 2" OD truss tube and has the industry compatible 14 mm thick base.

### Mega-Coupler Options -

- 1/2" x 1 1/4" Hex Head Bolt with Nylock Nut (Standard Mega-Coupler pictured above)
- 1/2" countersunk (CS) flat head bolt (see Mega-Coupler with Flat Head Bolt.)
- 3/8" countersunk (CS) flat head bolt (see Mega-Coupler with Flat Head Bolt)
- 3/8" x 1" Hex Head Bolt (3/8)
- 1/2" x 1 1/4" stainless steel (SS) bolt
- 1/2" x 1 1/4" steel wingnut (SW)

<b>Minimum Size</b>	1.25" pipe, 1.66" OD pipe
<b>Maximum Size</b>	1.5" pipe, 1.90" OD pipe, 2" OD truss tube
<b>Working Load Limit</b>	1,100 lb 500kg
<b>Hardware</b>	Standard hardware - 1/2-13 x 1 1/4" Hex Head grade 8 zinc plated steel bolt with nylock nut 1" Belleville Washer
<b>Weight</b>	1.2 Pounds
<b>Case Quantities</b>	24