




## BluCHIP EMR-16RELAY

BluCHIP EMR-16RELAY Elevator System I/O for up to 16 Total Floor Stops

The BluCHIP EMR-16RELAY is relay elevator system I/O that supports up to 16 floor stops. The kit is designed to be installed in an elevator machine room and works in conjunction with an EMR Controller kit. The kit is configured with space to add backup battery and utilizes an FPO power supply to generate 24VDC and a B100 to generate 12VDC. It includes one Mercury MR16OUT boards, a locking enclosure with tamper, power supply and wiring speed kit.



### System Features

#### FPO offline power supply

- 120 or 230 VAC input
- 12 and 24 VDC outputs
- On board Fire Alarm Interface
- Continuous and resettable DC

#### Distributed output module

- Four, controlled fused at 3A each
- Eight, auxiliary Class II P limited at 2.5A each

#### Expansion options

- Increased power, multiple voltages
- Additional distribution outputs
- Power management

### Specifications

#### Input Power:

- Input 120/230VAC 50/60Hz | 200 Watts
- Overload and short circuit protection
- Over temperature protection
- Polarized AC power supply disconnect

#### Output Power:

- 150W Total Output Power | 12VDC/12A or 24VDC/6A
- 5-18VDC @ 4A Max. | FPO Board Outputs: Continuous (DC1), Resettable (DC2)
- 8 Auxiliary Outputs, Class 2 PL @ 2.5A Each
- 120mV Output Voltage Ripple | System Efficiency: 88% | System BTU Rating: 66 BTU/Hr

#### Battery Charging:

- Independent built-in 2A (FPO150) Charger for sealed lead-acid or gel type batteries
- Microprocessor dual rate charging of 12 or 24V battery sets
- Automatic switchover to standby battery when AC fails
- Zero voltage drop when switched over to battery backup

### Enclosure Features

#### Labor saving design

- Unified power and security in one enclosure
- Pre-wired power section
- Removeable backplate simplifies installs
- Speed kit is included for power and data wiring
- Includes mounting studs on door to add additional I/O boards.

#### Additional benefits

- Wire management room
- 4.5" enclosure depth fits battery set
- Tamper switch, lock, dual key set standard
- Mounting hardware for access boards included

#### Regulatory Compliance:

- UL294, UL603, UL864, UL1076, UL1481, UL2044, UL2572, ULC S318, ULC S319, ULC S527
- CSA C22.2 #107.1, FCC Part 15, CSFM Approved


#### Access Panel:

- (1) MR16OUT  
16 Outputs

#### Size and Weight:

- 20.00"H x 16.00"W x 4.50"D | 23 lbs.

## Recommended board layout



## Kit Includes

| MFG Part # | BluBØX Order # | QTY | Description   |
|------------|----------------|-----|---|
| MR16OUT    | 120-2200       | 1   | Mercury MR16OUT: 16 Programmable Form C Relays 12/24VDC           |
| FPO150-E2M | 670-1320       | 1   | LifeSafety Power: Single voltage power supply, includes enclosure |

## Ordering Information

| BluBØX Order # | Description  |
|----------------|--|
| 753-3000       | BluCHIP EMR-16RELAY Elevator System I/O for up to 16 Total Floor Stops |

BluBØX: Security Re-Imagined

[www.blub0x.com](http://www.blub0x.com)

e. [info@blub0x.com](mailto:info@blub0x.com)

p. (844) 425-8209

FOLLOW US ON  

BluBØX Security, Inc. is a manufacturer and service provider of web-cloud based physical security products. Its BluSKY service delivers enterprise class unified access control, alarm management, video surveillance, biometrics and visitor management on any device, anywhere, any time. Its BluCHIP open hardware platform provides industry standard components and a proprietary line of fully integrated multi-factor, multi-biometric Person Readers.